

# SUREBONDER

**NEW  
in 2010!**

## Pneumatic Rivet Tool

### FPC815

### FPC815 Pneumatic Rivet Tool

This inexpensive pneumatic rivet tool can be used to set both aluminum and steel rivets ranging from 3/32" to 3/16". The 3/16" nosepiece is factory installed, also included and stored on bottom of rivet tool are the 3/32", 1/8", 5/32" nosepieces (3/16" stainless steel rivets not recommended). Made of lightweight die cast aluminum body. Includes a mandrel deflector for spent mandrels. Innovative 3 piece jaw design gives you a better grip and release of rivet mandrels. Long lasting seals to avoid oil leakage. Syringe to add oil to rivet tool when needed. Use for furniture, automotive, ductwork, sheet metal, gutters, etc.

### Specifications

Weight: 3 lbs.

Rivet Diameter Capacity: 3/32", 1/8", 5/32", 3/16"

Stroke: .562"

Air Pressure: 65-95 PSI

Pulling Force: 1100 lbs.



### Packaging:

Color Box

4 tools per master



FPC Corporation • 355 Hollow Hill Drive • Wauconda, IL 60084

Phone: (847) 487-4583 • Fax: (847) 487-0174 • www.surebonder.com • e-mail: sales@surebonder.com