



## PRO9000LT

Low Temperature

## Glue Gun

### Specifications

**Low Temperature:** 250°F. (121°C.)

**Watts Volts:** 200 Watts, 120 Volts

**Glue Stick Diameter:** 7/16" Regular .445" (11.3mm)

**Glue Stick Length:** 4", 10" & 15" (101.6mm, 254mm, 381mm)

**Case Pack:** 6 Master

**UPC #:** 018239322619

**Pounds Per Master:** 16 Pounds

**Glue Gun Weight:** 1.30 Pounds (20.8 ounces)

**Cubic Feet Per Master:** 1.7

**Master Case Size:** 14"x14"x17"

**Package Size:** 9"x11"x3"

**Packaged:** White Box



### PRO9000LT Low Temperature ( Industrial Glue Gun )

Industrial low temperature glue guns delivers 7 pounds of glue per hour with 200 watts of heating power. Stainless steel heater with thermostat temperature control for high output. Ergonomic design long trigger for less effort. Lighted on and off switch. Double insulated ground cord. Magnetic or wire stand keeps gun at the proper angle when idle. Exterior removable safety fuse for easy replacement.



FPC Corporation  
355 Hollow Hill Drive - Wauconda, IL 60084  
Phone: (847) 487- 4583, Fax: (847) 487-0174  
www.surebonder.com, e-mail: sales@surebonder.com