



PRO600

Temperature Controlled Pneumatic Glue Gun

Specifications

Adjustable Temperature: 284°F to 400°F. (120°C to 220°C.)

Watts Volts: 450 Watts, 120 Volts

Air Supply: 30-80 PSI

Glue Stick Diameter: 5/8" Regular (15mm)

Glue Stick Length: 10" (254mm)

Case Pack: 3 Master

UPC #: 018239338795

Glue Gun Weight: 9.05 Pounds

Package Size: 11.5"x8.5"x2.5"

Package: Black Plastic Case



PRO600 Temperature Controlled Glue Gun

Industrial pneumatic heavy duty temperature controlled glue gun with 450 watts of heating power. The pneumatic pistons feed the glue stick when the trigger is squeezed. Stroke adjustment screw allows same amount of glue per squeeze. The higher the wattage the more glue you can melt faster! Includes temperature controlled screwdriver, air regulator, 8" air hose with quick connector and storage case. Lighted ON/OFF switch, gun balancer mount hole, ergonomic trigger design for less fatigue. Exterior removable safety fuse for easy replacement. Interchangeable accessory nozzles also available.



FPC Corporation
355 Hollow Hill Drive - Wauconda, IL 60084
Phone: (847) 487-4583, Fax: (847) 487-0174
www.surebonder.com, e-mail: sales@surebonder.com